

# Polymer Precursors for Coatings, Binder and Adhesive Applications for Solid State Electrolytes

TECHNOLOGY NUMBER: 2019-033



## Technology ID

2019-033

## Category

Materials

Engineering & Physical Sciences

## Inventor

Eleni Temeche

Richard Laine

Xinyu Zhang

## Further information

Joohee Kim

jooheek@umich.edu

[View online](#)



## OVERVIEW

An improved method for incorporating LiPON materials onto solid state batteries

- An approach that is amenable to dip coating to substrates of interest
- A resulting product with improved ionic conductivities

## BACKGROUND

Short-circuits in batteries cause rapidly release all of stored energy and can cause heat release that is capable of igniting the flammable components within lithium ion batteries. One of the leading causes of short-circuits in lithium ion batteries is the uneven deposition of lithium ions on the anode, which can eventually bridge the anode to cathode. In an effort to address this issue, battery researchers have sought solid-state electrolytes that provide a physical barrier to dendrite formation. An attractive material for these applications is lithium phosphorous oxynitride (LiPON), a rigid ceramic material that resists dendrite penetration while providing lithium conductivity. Limitations to LiPON materials as solid-state electrolytes include the requirement for expensive manufacturing equipment which limits production scalability. Furthermore, LiPON has poor ionic conductivity compared to anode and cathode materials, minimizing the number of useful battery applications. So, a need exists for improved methods to build LiPON solid-state electrolytes to overcome current limitations.

## INNOVATION

Researchers have devised a method for producing solubilized phosphorous oxynitride (PON), lithium phosphorous oxynitride (LiPON), and silicon containing LiPON (LiSiPON) in a polymeric or oligometric state that is amenable to dip coating application to substrates of interest. Using

this approach, phosphorous oxychloride is first treated with  $\text{NaNH}_2$  to generate the PON precursor which is subsequently lithiated using  $\text{LiNH}_2$  at a 90% molar equivalence to the sodium amide from the previous step. The resulting material can be found to have a uniform deposition of LiPON with significantly improved ionic conductivities compared to conductivities observed for vapor deposited films. The ability to coat substrates of interest via dip coating offers a significantly more economical and readily scaled methodology for incorporating LiPON materials into solid-state batteries. These materials and this process can be utilized to employ LiPON as a binder, protective coating, or adhesive for the construction of solid-state batteries.

## PATENT APPLICATION

Number:US20210340011

## References

1. Zhang X, Temeche E, and Laine RM. , Synthesis, and Characterization of Polymer Precursors to  $\text{Li}_{x}\text{PON}$  and  $\text{Li}_{x}\text{SiPON}$  Glasses: Materials That Enable All-Solid-State Batteries (ASBs). *Macromolecules* 2020 53(7), 2702-2712 <https://doi.org/10.1021/acs.macromol.0c00254>
2. Temeche E, Zhang X, and Laine RM. , Precursor Derived  $\text{Li}_{x}\text{PON}$  Electrolytes: Toward Li-S Batteries. *ACS Applied Materials & Interfaces* 2020 12(18), 20548-20562. <https://doi.org/10.1021/acsami.0c03341>
3. Temeche E, Zhang X, and Laine RM. , Electrolytes for Li-S Batteries: Solid Solutions of Poly(ethylene oxide) with  $\text{Li}_{x}\text{PON}$ - and  $\text{Li}_{x}\text{SiPON}$ -Based Polymers. *ACS Applied Materials & Interfaces* 2020 12(27), 30353-30364 <https://doi.org/10.1021/acsami.0c06196>
4. Temeche E, Buch E, Zhang X, Brandt T, Hintennach A, and Laine RM. , Electrochemical Properties of  $\text{Li}_4\text{Ti}_5\text{O}_12$  Nanopowders (NPs) via Addition of  $\text{LiAlO}_2$  and  $\text{Li}_6\text{Si}_3\text{O}_4$  Polymer Electrolytes, Derived from Agricultural Waste, *ACS Applied Energy Materials* 2021 4(2), 1894-1905. <https://doi.org/10.1021/acsaelm.0c02994>